



In order to print the ring sizer above, be sure that your printer is set to 100%. Make sure that you have not reduced the print size in your printer 'page setup' area. You can verify that the sizer printed correctly by measuring it with a ruler; it should measure from A to B: 3 1/2 inches [88mm]long.

Once you have printed the sizer, follow these directions to find your ring size:

1. Cut out the ring sizer
2. Cut a slit for Slot "A"
3. With the numbers facing out, wrap the sizer around the finger where the ring will be worn.
4. Pull the pointed end Tab "B" through Slot "A" until the sizer is snug, making sure to allow size for the knuckle.
5. The number aligned with Slot "B" is your ring size.
6. If the measure lands between two numbers your size is a half size Ex: Between 5 and 6 ring size: 5.5. If half sizes are not available, order the next largest size.

Sizes are the closest equivalents possible						
U.S-Canada	Inside mm/inches [Diameter]	Inside mm/inches [Circumference]	Comparisons			
			Australian-U.K	France	Germany	Japanese
1½	12.78 / .503	40.2 / 1.580	C	40½	12¾	—
2	13.21 / .520	41.5 / 1.634	D	41½	13¾	2
2½	13.61 / .536	42.7 / 1.684	E	42¾	13¾	3
3	14.04 / .553	44.0 / 1.739	F	44	14	4
3½	14.45 / .569	45.2 / 1.788	G	45¼	14½	—
4	14.86 / .585	46.5 / 1.836	H½	46½	15	7
4½	15.27 / .601	47.8 / 1.888	I½	47¾	15¼	8
5	15.70 / .618	49.0 / 1.941	J½	49	15¾	9
5½	16.10 / .634	50.2 / 1.992	L	50¼	16	—
6	16.51 / .650	51.5 / 2.042	M	51½	16½	12
6¼	N/A	N/A	M ½	N/A	N/A	N/A
6½	16.92 / .666	52.8 / 2.092	N	52¾	17	13
7	17.35 / .683	54.0 / 2.146	N½	54	17¼	14
7½	17.63 / .699	55.3 / 2.196	O½	55½	17½	15
8	18.19 / .716	56.6 / 2.249	P½	56¾	18	16
8½	18.59 / .732	57.8 / 2.300	Q½	58	18½	17
9	18.99 / .748	59.1 / 2.350	R½	59¼	19	18
9½	19.41 / .764	60.3 / 2.400	S½	60½	19½	19
10	19.84 / .781	61.6 / 2.463	T½	61¼	20	20
10½	20.24 / .797	62.8 / 2.504	U½	62¾	20¼	22
11	20.68 / .814	64.1 / 2.567	V½	64¼	20¾	23
11½	21.01 / .830	66.0 / 2.608	W½	66	21	24
12	21.41 / .846	67.3 / 2.658	Y	67¼	21½	25